

Aquaporin Inside[®] Membranes

Tap Water Reverse Osmosis Element



- ✓ Revolutionary high water flow for most efficient water treatment
- ✓ Enables water treatment with low energy consumption
- ✓ High rejection of harmful pollutants ensures safe and healthy drinking water
- ✓ Manufactured using Nature's water channels

Product type

The Aquaporin Inside[®] Tap Water Reverse Osmosis (TWRO) membrane element is produced with aquaporin proteins, Nature's own water filter. It is the aquaporin protein that provides Aquaporin Inside[®] membranes with its unique properties.

All Aquaporin Inside[®] TWRO membranes are available in standard configurations and can easily fit into any point-of-use residential or commercial RO system.


Product specifications

Product name	Permeate flow rate		Minimum salt rejection (%)	Stabilized salt rejection (%)	Applied pressure (psi)	Recovery (%)
	GPD	L/h				
TWRO3012-600	600	95	92	96	80	40

The stated product performances are based on 250 ppm NaCl solution at 25°C / 77°F. Individual element permeate flow rate may vary ± 15%.

TWRO3012-600

Element dimensions



Product name	Dimensions (inches / millimeters)				
	A	B	C	D	E
TWRO3012-600	11.73 / 298.0	0.87 / 22.0	0.67 / 17.0	2.91 / 74.0	9.96 / 253.0

Aquaporin A/S reserves the right to change specifications without prior notice.
 TWRO3012-600 elements fit standard 3012 pressure vessels with nominal 80 mm (3.15 inches) inner diameter.

Operating specifications

Maximum operating pressure	145 psi (10 bar)	Maximum feed water SDI	5 (15 min)
Maximum operating temperature	45°C (113°F)	Maximum feed water turbidity	1 NTU
Maximum feed flow rate	2.5 gpm (9.5 lpm)	pH range	3-10
Maximum pressure drop	10 psi (0.7 bar)	Free chlorine tolerance	< 0.1 ppm

Additional information

- ✓ Permeate from the first hour of operation should be discarded.
- ✓ To prevent biological growth during prolonged system shutdowns, it is recommended that membrane elements be immersed in a preservative solution. Rinse out the preservative solution before use. See Aquaporin's storage recommendations for TWRO elements for more details.
- ✓ Elements contained in the boxes must be kept dry at room temperature (7-32°C / 40-95°F) and should not be stored in direct sunlight.
- ✓ Keep elements moist at all times after initial wetting.
- ✓ The presence of free chlorine and other oxidizing agents can cause premature membrane failure. Since oxidation damage is not covered under warranty, Aquaporin A/S recommends removing residual free chlorine by pretreatment prior to membrane exposure.
- ✓ The information provided in this document is for informative purposes only. It is the responsibility of the user to ensure appropriate usage of this product. Aquaporin A/S assumes no obligation, liability, or damages incurred for the misuse of the product or for the information provided in this document. This document does not express or imply any warranty as to the merchantability or fitness of the products.

Aquaporin A/S
 Nymøllevej 78
 2800 Kongens Lyngby
 Denmark

Phone: +45 8230 3082
 sales@aquaporin.com
 www.aquaporin.com

Aquaporin Asia Pte Ltd
 1 Cleantech Loop, #02-14
 Cleantech One
 Singapore 637141

Phone: +65 6268 6343
 sales@aquaporin.asia

Aquapoten Company Ltd.
 12A Shougang International Trade Tower
 No. 60 Xizhimen North Street
 Haidian District, Beijing, 100082, China

Phone: +86-10-52408461
 business@aquapoten.com
 www.aquapoten.com

